

KoskiFutura

Antislip



Flooring panel with hard wearing surface

KoskiFutura Antislip is strong Finnish Birch Plywood with a durable, glass fibre reinforced, slip resistant coating containing quartz granules. The slip resistant finish is ideal for demanding applications in the transport industry. The hard wearing coating also protects the plywood against moisture penetration,

KoskiFutura Antislip is suitable especially for vehicle floors, loading ramps and platforms, trailers, recreational vehicles, sports hall and playground facilities, suitable for indoor and outdoor uses, flooring of cold storage rooms.



ECO-FRIENDLY



HEAT RESISTANT



ANTISLIP



LOAD BEARING CAPACITY



SAFETY OF FOOD

-  Slip resistant surface, rating R12 (DIN 51130)
-  Environmentally friendly product (contains no chlorine derivatives)
-  Very durable wear resistant surface
-  Heat resistant from -30° to +80°
-  Good colour stability (6-7 according to DIN 54004)
-  High load bearing capacity
-  Certified food safe



KOSKISEN

KoskiFutura

Antislip



Technical specifications

| | |
|-----------------------------|--|
| Base plywood | Koskisen Finnish birch plywood |
| Bonding | Phenolic resin according to EN 314-2/ class 3 exterior conditions Formaldehyde emission levels of panels fulfil requirements of Class E1 (EN13986), CARB Phase II, ULEF (Ultra Low Emitting Formaldehyde) |
| Coating | Fibre reinforced coating with quartz granules, available in black (RAL 9005) and grey (RAL 7043), the reverse can be overlaid with various coatings depending upon the final application. |
| Standard thicknesses | 9, 12, 15, 18, 21, 24, 27 and 30 mm |
| Standard sizes | 1220 x 2400-3600 mm 1525 x 2400-3600 mm |
| Density | Approx 700 kg/m ³ |
| Edge treatment | Acrylic paint against moisture pick up |
| Wear resistance | Taber value 32 250 R according to EN438-2 |
| Wheel test value | Approx 225 000 cycles with a load of 300 kg (SFS 3939) |
| Other data | Detailed technical values can be found in Koskisen's Declaration of Performance (DoP). Please visit koskisen.com/download . |

Additional information

Environment

Our raw material, wood is an ecological and renewable material and it stores carbon during its whole life cycle. Koskisen plywood products are manufactured in Finland according to the strictest sustainability principles. Koskisen is a pioneer in the Finnish forest industry in paying attention to the environment and the wood's supply chain is always known in detail. Finnish forests are primarily privately owned and the owners are guided by a strong commitment to long-term forestry and forest cultivation. Yearly, Finnish forests grow more than they are harvested. This guarantees a sustainable and environmentally sound raw material.

Additional information

Wood is a living material and every panel is unique. Therefore a photograph or a sample piece cannot represent a full sized panel as regards colours, shades, figure, knots etc. Please note that a slight colour variation is accepted between panels.

The information, although based on extensive testing, is intended as a guideline only and comes without warranty. We reserve the right to amend specifications without notice. Any defects other than those caused by clearly verified production or service faults by the supplier are the responsibility of the user. Any claim for compensation is limited to the value of the defective panels. The Seller makes no guarantee that the goods are fit for a particular purpose, unless it provides a written declaration of their suitability.



Koskisen Panel Industry

Tehdastie 2, 16600 Järvelä, FINLAND
tel. +358 20 553 41
koskisen.com

